

25
JAGUAR



Forage Harvester

JAGUAR 25

- Two stage Foldable Chute
- In-built Sharpening Tool
- Feed Rollers with overload protection
- Self sharpening cutting Disc
- Powerful discharge.
- Reliable and Durable Gearbox
- Discharge Chute Extension.

Affordable solution for quality silage

CLAAS

Specification			
No. of Rows			1
Lower Linkage Mounting Category			CAT II
Tractor Power Requirement	HP	45-60	[Depending on the crop, field and trolley conditions.]
PTO	RPM	540	
Chopping			
Disc Flywheel Diameter	mm	690	
Disc Flywheel/Blower Speed	rpm	1450	
Chopping Length	mm	5-7	
No. of Knives/Blade		12	
No. of Feed Rollers		2	
Discharge Chute			
Swivel Range			
Manual adjustment	Degree	360	
Remote adjustment	Degree	120	
Position adjustment			Mechanical
Angle adjustment			Mechanical
Foldable			2 Fold
Dimensions			
Length	m	2.5	
Width	m	2.6	
Height (Working Position)	m	3.2	
Height (Transport Position-Upper Chute Foldable)	m	2.1	
Weight	Kg	520	
Other Features:			
In Built Knife/Blade Sharpening Tool			Standard
Overload Protection			Standard
Trolley Hitch			Standard

CLAAS continually develops its products to meet customer's requirements, so all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications.



Large Grinding Stone:

Covers the full width of the knives and ensures knives are sharpened from end to end.




Self-Sharpening Cutting Discs:

No matter how fast you drive, your JAGUAR 25 will leave clean stubble behind it. Self-sharpening rotating cutting discs cut the maize plants cleanly and low down.



Powerful discharge:

Behind each of 12 knives, there is an impeller blade which gives a powerful thrust to the chopped forage material to blow into the trolley.



Reliable and Durable Gearbox:

Designed with heavy duty material like bearings, seals, other crucial parts and overload protection gears.



Tractor Mounted Discharge Chute Control:

Discharge chute can be controlled mechanically from the operator's seat, with arrangement of both trailed and parallel trolley loading operations.

CLAAS Agricultural Machinery Private Limited
 487/B1, 14th Cross, 4th Phase
 Peenya Industrial Area, Bangalore – 560058, Karnataka
 Tel: +91-80-67167000

E-mail: marketing.india@claas.com
www.claas.co.in

/CLAASinIndia /channel/CLAASinIndia

For any queries
CLAAS CARE
 1800 425 25227